

呼び名	コンクリート				PC鋼線			参考重量 W (kg)	設定曲げモーメント		
	長さ L (mm)	幅 B (mm)	厚さ T (mm)	断面積 Ac×10 ² (mm2)	径 φ (mm)	本数 (本)	断面積 Ap (mm2)		活荷重 Mσ (kN-m)	一輪荷重 Mσ (kN-m)	自重 Mdo (kN-m)
T-2											
T0210	1000	1000	80	800	9.3	6	309.66	200	2.26	2.57	0.21
T0215	1500	1000	80	800	9.3	8	412.88	300	3.14	3.95	0.50
T0220	2000	1000	80	800	9.3	10	516.10	400	4.02	5.32	0.91
T0225	2500	1000	80	800	9.3	12	619.32	500	4.90	6.69	1.44
T0230	3000	1000	100	1000	9.3	10	516.10	750	6.15	8.00	2.58
T0235	3500	1000	100	1000	9.3	12	619.32	880	8.41	9.35	3.55
T0240	4000	1000	120	1200	12.7	6	592.26	1200	10.90	10.65	5.54
T0245	4500	1000	120	1200	12.7	6	592.26	1350	13.83	11.99	7.06
T0250	5000	1000	140	1400	12.7	6	592.26	1750	16.95	13.27	10.13
T0255	5500	1000	140	1400	12.7	8	789.68	1930	20.53	14.60	12.32
T0260	6000	1000	140	1400	12.7	10	987.10	2100	24.44	15.92	14.73
T0265	6500	1000	140	1400	12.7	12	1184.52	2280	28.66	17.24	17.35
T0270	7000	1000	160	1600	12.7	2+12	1381.94	2800	32.96	18.50	22.93
T0275	7500	1000	160	1600	12.7	2+14	1579.36	3000	37.68	19.81	26.40
T0280	8000	1000	180	1800	12.7	2+12	1381.94	3600	42.46	21.05	33.72
T0285	8500	1000	180	1800	12.7	2+14	1579.36	3830	47.68	22.35	38.16
T0290	9000	1000	200	2000	12.7	2+12	1381.94	4500	52.93	23.59	47.44
T0295	9500	1000	200	2000	12.7	2+14	1579.36	4750	58.64	24.88	52.98
T02100	10000	1000	220	2200	12.7	2+14	1579.36	5500	64.36	26.11	64.45
T02105	10500	1000	240	2400	12.7	2+14	1579.36	6300	70.30	27.34	77.38
T-6											
T0610	1000	1000	80	800	9.3	10	516.10	200	6.78	7.69	0.21
T0615	1500	1000	100	1000	9.3	12	619.32	380	9.32	11.67	0.61
T0620	2000	1000	120	1200	12.7	6	592.26	600	11.85	15.63	1.30
T0625	2500	1000	120	1200	12.7	8	789.68	750	14.49	19.74	2.09
T0630	3000	1000	120	1200	12.7	10	987.10	900	17.33	23.82	3.05
T0635	3500	1000	140	1400	12.7	8	789.68	1230	20.16	27.72	4.85
T0640	4000	1000	140	1400	12.7	10	987.10	1400	23.10	31.76	6.39
T0645	4500	1000	140	1400	12.7	12	1184.52	1580	26.03	35.79	8.16
T0650	5000	1000	160	1600	12.7	2+10	1184.52	2000	28.83	39.64	11.48
T0655	5500	1000	160	1600	12.7	2+10	1184.52	2200	31.73	43.62	13.98
T0660	6000	1000	160	1600	12.7	2+12	1381.94	2400	34.62	47.60	16.72
T0665	6500	1000	180	1800	12.7	2+10	1184.52	2930	38.83	51.39	22.02
T0670	7000	1000	180	1800	12.7	2+12	1381.94	3150	44.82	55.33	25.64
T0675	7500	1000	180	1800	12.7	2+14	1579.36	3380	51.06	59.25	29.54
T0680	8000	1000	200	2000	12.7	2+12	1381.94	4000	57.29	63.00	37.27
T0685	8500	1000	200	2000	12.7	2+14	1579.36	4250	64.00	66.89	42.20
T0690	9000	1000	220	2200	12.7	2+14	1579.36	4950	70.68	70.61	51.94
T0695	9500	1000	240	2400	12.7	2+14	1579.36	5700	77.58	74.32	63.03
T06100	10000	1000	260	2600	12.7	2+14	1579.36	6500	84.71	78.01	75.54
T06105	10500	1000	280	2800	12.7	2+14	1579.36	7350	92.05	81.69	89.57

呼び名	コンクリート				PC鋼線			重量 W (kg)	設定曲げモーメント		
	長さ L (mm)	幅 B (mm)	厚さ T (mm)	断面積 Ac×10 ² (mm2)	径 φ (mm)	本数 (本)	断面積 Ap (mm2)		活荷重 Mσ (kN-m)	一輪荷重 Mδ (kN-m)	自重 Mdo (kN-m)
T-14											
T1410	1000	1000	120	1200	12.7	6	592.26	300	15.33	17.17	0.29
T1415	1500	1000	140	1400	12.7	6	592.26	530	21.24	26.46	0.80
T1420	2000	1000	140	1400	12.7	10	987.10	700	27.40	36.09	1.49
T1425	2500	1000	160	1600	12.7	2+10	1184.52	1000	33.31	45.28	2.69
T1430	3000	1000	160	1600	12.7	2+12	1381.94	1200	39.87	54.81	3.96
T1435	3500	1000	180	1800	12.7	2+12	1381.94	1580	46.49	63.92	6.08
T1440	4000	1000	180	1800	12.7	2+14	1579.36	1800	53.35	73.36	8.05
T1445	4500	1000	200	2000	12.7	2+14	1579.36	2250	59.91	82.38	11.33
T1450	5000	1000	220	2200	12.7	2+12	1381.94	2750	66.44	91.36	15.40
T1455	5500	1000	220	2200	12.7	2+14	1579.36	3030	73.22	100.67	18.79
T1460	6000	1000	240	2400	12.7	2+14	1579.36	3600	79.69	109.57	24.39
T1465	6500	1000	260	2600	12.7	2+14	1579.36	4230	86.13	118.43	31.01
T1470	7000	1000	260	2600	12.7	2+14	1579.36	4550	92.82	127.63	36.18
T1475	7500	1000	280	2800	12.7	2+14	1579.36	5250	99.21	136.41	44.71
T1480	8000	1000	300	3000	12.7	2+14	1579.36	6000	105.58	145.17	54.48
T1485	8500	1000	320	3200	12.7	2+14	1579.36	6800	111.93	153.90	65.58
T1490	9000	1000	340	3400	12.7	2+2+12	1579.36	7650	118.24	162.58	78.09
T1495	9500	1000	340	3400	12.7	2+2+14	1776.78	8080	124.80	171.60	87.37
T14100	10000	1000	340	3400	12.7	2+2+14	1776.78	8500	131.33	180.58	97.17
T14105	10500	1000	360	3600	12.7	2+2+14	1776.78	9450	137.59	189.18	113.36
T-25											
T2510	1000	1000	140	1400	12.7	10	987.10	350	26.92	29.96	0.32
T2515	1500	1000	160	1600	12.7	2+10	1184.52	600	37.48	46.56	0.88
T2520	2000	1000	180	1800	12.7	2+12	1381.94	900	48.04	63.07	1.83
T2525	2500	1000	200	2000	12.7	2+12	1381.94	1250	58.60	79.49	3.25
T2530	3000	1000	220	2200	12.7	2+12	1381.94	1650	69.70	95.84	5.21
T2535	3500	1000	240	2400	12.7	2+12	1381.94	2100	81.53	112.11	7.82
T2540	4000	1000	260	2600	12.7	2+14	1579.36	2600	93.31	128.31	11.14
T2545	4500	1000	300	3000	12.7	2+12	1381.94	3380	104.55	143.75	16.21
T2550	5000	1000	300	3000	12.7	2+14	1579.36	3750	116.70	160.46	20.30
T2555	5500	1000	320	3200	12.7	2+14	1579.36	4400	128.33	176.45	26.30
T2560	6000	1000	340	3400	12.7	2+2+12	1579.36	5100	139.89	192.35	33.36
T2565	6500	1000	340	3400	12.7	2+2+14	1776.78	5530	151.89	208.84	39.52
T2570	7000	1000	340	3400	12.7	2+4+14	1974.20	5950	163.84	225.28	46.19
T2575	7500	1000	340	3400	12.7	2+6+14	2171.62	6380	175.74	241.64	53.39
T2580	8000	1000	360	3600	12.7	2+6+14	2171.62	7200	187.12	257.28	64.36
T2585	8500	1000	380	3800	12.7	2+6+14	2171.62	8080	198.44	272.86	76.74
T2590	9000	1000	400	4000	12.7	2+6+14	2171.62	9000	209.74	288.38	90.61
T2595	9500	1000	420	4200	12.7	2+6+14	2171.62	9980	220.98	303.84	106.05
T25100	10000	1000	440	4400	12.7	2+6+14	2171.62	11000	232.19	319.26	123.16